


SYSTEM SETTING MODE "SYS" (1/3)

Select "SYS" to enter the system setting mode




Set each item by pressing

Up/Down to change the setting

Enter to confirm and proceed to the next item

SYSTEM SETTING MODE "SYS" (2/3)

Aspirating and dispensing speeds




Buzzer ON/OFF




SYSTEM SETTING MODE "SYS" (3/3)

BlowoutONOFF


Reverse operation






STANDARD MODE "AUTO"

Select "AUTO" to enter the standard mode




Set the dispensing volume (μl*)




MULTIPLE DISPENSING MODE "MD"

Select "MD" to enter the multiple dispensing mode



 Set the volume for one dispensing (µI) and the number of dispensings (COUNT)






For multiple dispensing the reverse operation is automatically selected




MIXING MODE "MIX"

Select "MIX" to enter the mixing mode



Set the number of mixes (COUNT) and mixing volume (μl)









DISPENSING AND MIXING MODE "AUTO+MIX" (1/2)

 Select "AUTO" and hold down the Enter key (for approx. 3 seconds) until "MIX" lights up to enter the dispensing and mixing mode




DISPENSING AND MIXING MODE "AUTO+MIX" (2/2)

Set the dispensing volume (μl)



Set the number of mixes (COUNT) and mixing volume (μl)









SEQUENTIAL ASPIRATING MODE "SA" (1/2)

 Select "MIX" and hold down the Up key (for approx. 3 seconds) until "SE" starts flashing




Have "SA" displayed and enter the sequential aspirating mode




SEQUENTIAL ASPIRATING MODE "SA" (2/2)

 Set the first, second, third (and further required) aspirating volumes (µI) in order



 Press the Enter key* while "---" is displayed after all the required volumes are set




* Setting will automatically terminate when the sum of all the aspirating volumes and air gaps (for the MPA-10/20/200 only) reached the pipette's maximum volume


Enter

SEQUENTIAL DISPENSING MODE "SD" (1/2)

 Select "MIX" and hold down the Up key (for approx. 3 seconds) until "SE" starts flashing




Switch "SA" to "Sd" and enter the sequential dispensing mode




SEQUENTIAL DISPENSING MODE "SD" (2/2)

 Set the first, second, third (and further required) dispensing volumes (µI) in order



 Press the Enter key* while "---" is displayed after all the required volumes are set



* Setting will automatically terminate when the sum of all the dispensing volumes reached the pipette's maximum volume